

Certificate of constancy of performance



Number

0620-CPR-82705/03

Replaces

0620-CPR-82705/02

Issued

01/05/2022

First issued

08-05-2014

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

Corrugated safety metal hose assemblies for the connection domestic appliance using gaseous fuels

whereby the scope of construction product(s) is listed on page 2 of this certificate placed on the market under the name or trademark of

Maral Sri

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

EN 14800:2007

under system 1 for the performances set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

This certificate was first issued on May 8th 2014 will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

/200504

Ron Scheepers Managing Director Kiwa

Advise consult www.kiwa.nl to check whether the certificate is valid.

Notified Body No. 0063 Kiwa Nederland B.V.

Sir Winston Churchilllaan 273 Postbus 70

2280 AB RIJSWIJK

The Netherlands

Tel. +31 (0) 88 998 44 00 Fax +31 (0) 88 998 44 20 info@kiwa.nl www.1kiwa.com

PRODUCTS RVA C 002 Manufacturer (Head Office)

Maral Srl Via Fogazzaro 52 20831 Seregno Italy

T: +39 03 62 32 26 60

F; +39 03 62 32 62 69 E: sales@maraltubi.com I: www.maraltubi.com Manufacturer (Factory address)

52



Certificate of constancy of performance



0620-CPR-82705/03

Corrugated safety metal hose assemblies for the connection domestic appliance using gaseous fuels

SCOPE

Corrugated safety metal hose type "TSGAS".

Connection:

1/2 " male gas thread ISO 7 and 1/2" female swivel straight or with elbow connection

Gas hose length:

500, 750, 1000, 1250, 1500 and 2000 mm.

